



Network Power supply with battery backup, 12Vdc, 1A, CEE7, lithium battery

CP12010LI-GR

Οv	er	VI	e	V	V
----	----	----	---	---	---

Lead time	Usually in Stock
Main	
Main Input Voltage	220 V 230 V 240 V
Main Output Voltage	12 V DC
Rated power in W	12 W
Rated power in VA	12 VA
Battery type	Li-lon (Lithium-lon)

Physical

_	
Height	7.8 cm
Width	4.8 cm
Depth	7.6 cm
Net weight	0.2 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Output

Maximum configurable power in 12 W W

Conformance

Standarda	EN 55024	
Standards	EN 33024	
	EN 60950	

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	595 %

Ambient air temperature for storage	-1560 °C

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0

Packing Units

Package 1 Weight	0.28 kg
Package 1 Height	11.3 cm
Package 1 width	5.2 cm
Package 1 Length	9.9 cm
SCC14	10731304344091
Number of Units in Package 2	56
Package 2 Weight	15.68 kg
Package 2 Height	203.20 mm
Package 2 width	381.00 mm
Package 2 Length	457.20 mm
Number of Units in Package 3	1680
Package 3 Height	320.04 cm
Package 3 width	254 cm
Package 3 Length	3048 cm

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------