

# i-SENSYS MF3010 Specifications

## Product Specification

### TYPE

Machine Type	Mono Laser All-in-One
Available Functions	Print, Copy and Scan

### PRINTER

Print Speed	Up to 18 ppm (A4)
Printing Method	Monochrome laser beam printing
Print Quality	Up to 1200 x 600 dpi with Automatic Image Refinement
Print Resolution	600 x 400 dpi
First Print Out Time	7.8 secs
Printer Languages	UFR II-LT
Print Margins	5 mm-top, 6 mm- bottom, 5 mm-left and right
Toner Saver Mode	Yes

### COPIER

Copy Speed	Up to 18 ppm (A4)
First Copy Output Time (FCOT)	Approx. 12 seconds or less
Copy Resolution	Up to 600 x 600 dpi
Copy Modes	Text, Text/Photo, Text/Photo+, Photo
Multiple Copy	Up to 9 copies
Reduction / Enlargement	50-200% in 10% increments
Toner Saver Mode	No
Other Features	2 on 1, ID Card Copy

### SCANNER

Type	Colour
Scan Resolution	Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi
Colour Scanning Depth	24 bit/24 bit (input/output)
Greyscales	256 levels
Compatibility	TWAIN, WIA
Max. Scan Width	216 mm

### MEDIA HANDLING

Scanner Type	Flatbed
Paper Input (Standard)	150-sheet tray
Paper Output	100-sheet
Media Types	Plain paper, Heavy paper, Recycled paper, Transparency, Label, Envelope, Index Card
Media Sizes	Tray: A4, B5, A5, Executive, Envelope (COM10, Monarch, DL, B5, C5), LTR, LGL, Statement, Custom sizes: Width 76 x 216 mm; Length 127 x 356 mm.
Media Weights	Tray: 60 to 163 g/m <sup>2</sup>

### INTERFACE & SOFTWARE

Interface Type	USB 2.0 Hi-speed
Operating System Compatibility	Windows 7/2000/ XP/ Vista Mac OS X Version 10.4.9 - 10.7.x <sup>1</sup> Linux <sup>2</sup>
Software and Printer Management	Presto! Page Manager, MF Toolbox

### GENERAL FEATURES

Duty Cycle	Max. 8,000 pages per month
Warm-up Time	Approx. 10 seconds from power on
Memory	64 MB
Control Panel	1 digit LED

<b>Dimensions with Trays (W x D x H)</b>	372 mm x 276 mm x 254 mm
<b>Installation Space (W x D x H)</b>	572 mm x 632 mm x 608 mm
<b>Weight</b>	8.2 Kg
<b>Operating Environment</b>	Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation)
<b>Power Source</b>	220-240 V (±10%), 50/60 Hz (±2 Hz)
<b>Power Consumption</b>	Maximum: Approx. 960W Active: Approx. 450W Sleep mode: Approx. 1.4 W Typical Electricity Consumption (TEC): 0.6 kWh
<b>Noise Levels</b>	Sound Power Active: 65.3dB or less, Standby: 43.0dB or less Sound Pressure Active: 50.4dB, Standby: Inaudible

## CONSUMABLES

<b>Cartridges</b>	Cartridge 725 (1,600 pages <sup>1</sup> ) <sup>2</sup>
Operating System Compatibility	<sup>1</sup> Web distribution only. Driver release November 2011 <sup>2</sup> Web distribution only. Linux support printing only. Driver release January 2012
Cartridges	<sup>1</sup> Ships with 700 pages starter cartridge <sup>2</sup> Based on ISO/IEC 19752

All specifications subject to change without notice