Synology[®]

Deep Learning NVR

DVA3221



Deep Learning Video Analytics

Synology NVR DVA3221 is an on-premises 4-bay desktop NVR solution that integrates Synology's deep learning-based algorithms to provide a fast, smart, and accurate video surveillance solution. Built-in support for push notifications keeps users informed of possible intrusions, while the automated video surveillance system helps safeguard properties by detecting people, vehicles, and anonymous objects in designated areas.

Highlights

· Facial Recognition

Provide enhanced tracking and greater security by categorizing and then identifying personnel in real-time

• People & Vehicle Detection

Build situational awareness by detecting people or vehicles in off-limit areas

People Counting

Measure marketing effectiveness and optimize rental prices by monitoring foot traffic

· Intrusion Detection

Setup perimeter lines for automatic notifications when breaches occur

• Easy and Flexible Integration

Complete surveillance deployments in no time with support for over 7,600 IP cameras, H.264/H.265, and 4K resolution¹

· Cross-Platform Support

Access from anywhere and anytime with Windows®, macOS®, iOS™, Android® and web browser support

· Scalable Storage

Expand with up to two DX517 expansion units for an additional 10 drive bays²



Safeguarding Your Assets

Surveillance Station delivers intelligent monitoring and video management tools to protect your property and assets.



Smarter On-premises Security

Synology DVA and Surveillance Station elevate video surveillance into a real-time security solution, providing instant feedback and notifications.

Next-generation Surveillance Solution with Deep Learning Technology

- **Event surveillance**: Create a custom watchlist by importing photos of attendees into a database and set rules to notify system administrators when personnel or a VIP client enters or leaves the compound.
- **Suspicious tracking**: Capture and register, or manually submit photos of an unknown person into a database to search for footage of them, or to be alerted when they re-appear on camera.
- **Covered face detection**: Detect when a person is or is not wearing a mask and be notified.
- Flexible storage and camera channels: Expand storage to 10 extra drive bays using two Synology DX517 expansion units. Install up to 32 IP camera channels³ using 12 real-time video analysis tasks.

Generate Actionable Insights

Advanced deep learning-based algorithms built into the DVA3221 convert vast amounts of unstructured video data into business intelligence and security insights. This helps significantly reduce workloads while enhancing overall security.

- **Facial recognition**: Instantly identify key personnel in a custom database with an accuracy of 97.04%⁴.
- **People and vehicle detection**: Notify administrators when an anonymous person or vehicle is loitering in a pre-defined area such as a no-parking zone or in front of a shop.
- **People counting**: Count the number of people entering and exiting in an area using bidirectional counters to help owners gauge sales and marketing effectiveness, or adjust rental rates.
- **Intrusion detection**: Detect when a person or vehicle crosses a perimeter line, alerting administrators to potential intrusions.





Surveillance On-the-Go

With DS cam, you can watch surveillance video feeds, take snapshots, zoom in and adjust camera position with PTZ control, browse through recorded events, and receive instant notifications on-the-go.

Powerful VMS Platform

Powered by Synology **Surveillance Station** running on Synology DSM, the DVA3221 combines powerful video analytics with robust storage and data management capabilities.

- Complete data ownership with zero subscription fees: Unlike security cameras that require monthly subscriptions and store data on the cloud, all DVA3221 recordings are privately stored on the unit itself, free of charge.
- Works with more than 7,600 cameras: No lock-ins. Choose from a wider range of camera options to suit your requirements with ONVIF support.
- Remote monitoring and control: Access your surveillance system anytime, anywhere, from a web browser, desktop client, or the DS cam mobile app.
- Automation & notification: Set up custom actions when predefined events occur, such as automatically taking snapshots when motion is detected. Get notified with e-mail, SMS, or push notifications so that you can respond in a timely manner.
- Data Protection and CMS: Comprehensive data protection and backup tools included for both on-site, remote, or cloud-based backup targets. Set up and manage multi-site surveillance systems easily, with optional N+M failover for maximum service availability.⁵



Hardware Overview

Front

Rear



1	Drive tray and status indicator	2	Status indicator	3	Alert indicator	4	LAN indicator
5	Drive tray lock	6	Power button and indicator	7	USB 3.2 Gen 1 port	8	System fan
9	Power port	10	Kensington Security Slot	11	Console port	12	Reset button
13	eSATA port	14	1GbE RJ-45 port				

Technical Specifications

Hardware

Relative humidity Maximum operating altitude	5% to 95% RH 5,000 m (16,400 ft)
Storage temperature	-20 °C to 60 °C (-5 °F to 140 °F)
Operating temperature	0°C to 40°C (32°F to 104°F)
Power frequency	50/60Hz, single phase
AC input power voltage	100V to 240V AC
System fan	1 (120 x 120 x 25 mm)
Scheduled power on/off	Yes
Wake on LAN/WAN	Yes
LAN port	4 x 1GbE RJ-45
Weight	4.92 kg
Size (HxWxD)	166 x 250 x 237 mm
External port	 3 x USB 3.2 Gen 1 port 2 x eSATA port 1 x COM (for POS system connection)
Hot swappable drive	Yes
Compatible drive type	4 x 3.5" or 2.5" SATA HDD/SSD (drives not included)
Memory	8 GB DDR4 non-ECC SO-DIMM (4 GB x 2; expandable up to 32 GB with 16 GB ECC SO-DIMM x 2) 7
GPU	NVIDIA® GeForce® GTX 16506
Hardware encryption engine	Yes (AES-NI)
CPU	Intel® Atom C3538 Quad-core 2.1GHz



General DSM specification

General DSM specification	·
Networking protocol	SMB, AFP, NFS, FTP, WebDAV, CalDAV, iSCSI, Telnet, SSH, SNMP, VPN (PPTP, OpenVPN™, L2TP)
File system	 Internal: Btrfs, ext4 External: Btrfs, ext4, ext3, FAT, NTFS, HFS+, exFAT⁸
Supported RAID type	Synology Hybrid RAID (SHR), Basic, JBOD, RAID 0, RAID 1, RAID 5, RAID 6, RAID 10
Storage management	 Maximum single volume size: 108TB Maximum system snapshots: 65,536° Maximum internal volume: 64
SSD cache	Read/write cache support
File sharing capability	 Maximum local user account: 2,048 Maximum local group: 256 Maximum shared folder: 512 Maximum concurrent SMB/NFS/AFP/FTP connection: 2,000
Privilege	Windows Access Control List (ACL), application privileges
Directory service	Windows® AD integration: Domain users login via SMB/NFS/AFP/FTP/File Station, LDAP integration
Security	Firewall, shared folder encryption, SMB encryption, FTP over SSL/TLS, SFTP, rsync over SSH, login auto block, Let's Encrypt support, HTTPS (customizable cipher suite)
Supported client	Windows® 7 onwards, macOS® 10.12 onwards
Supported browser	Chrome®
Interface language	English, Deutsch, Français, Italiano, Español, Dansk, Norsk, Svensk, Nederlands, Русский, Polski, Magyar, Português do Brasil, Português Europeu, Türkçe, Český, ภาษาไทย, 日本語, 한국어, 繁體中文, 简体中文
Surveillance Station	
Maximum IP camera	 32 channels (total of 960 FPS at 720p, H.264), including a maximum of 12 real-time Deep Video Analytics tasks¹⁰ 8 free camera licenses included; additional cameras require the purchasing of additional licenses
Deep video analytics feature	 Face recognition People counting People and vehicle detection Intrusion detection
IP Camera support	 Video codec: MJPEG, MPEG-4, H.264, H.265, and MxPEG (not supported by Deep Video Analytics tasks) Audio codec: PCM, AAC, AMR, G.711, and G.726 Camera bit-rate fine-tuning via constant and variable bit-rate control ONVIF™ 2.6, Profile S certified, Profile G for edge recording
Live View	 Pan Tilt Zoom (PTZ) support with configurable PTZ speed On-screen camera controls: camera zoom, focus, iris adjustment, auto pan, and auto object tracking E-Map, Snapshot, and Snapshot Editor supported for instant editing after taking a snapshot Video quality settings: bit-rate control, image quality, resolution, and FPS Joystick support for easy navigation Alert panel for a quick display of the most recently triggered events Customizable layout and sequential camera view support
Recording	 Supported recording modes: manual, continuous, motion detection, I/O alarm, action rule, and customized Recording formats: MP4 The customized recording mode can be configured as a combination of conditional events, including motion detection, audio detection, tampering detection, and alarm input Edge recording on the SD card of certain supported cameras Configurable pre-recording and post-recording time
Playback	 Customizable layouts for playback in Timeline Playback controls include pause, stop, previous recording, next recording, fast forward, slow motion, frame by frame, and digital zoom in/out Embedded watermark for evidence integrity Image enhancements including brightness, contrast, saturation, and sharpness (web client only)
Management	 Create and manage different user privileges Rotate recorded videos by archived days or storage size Event notification supported via SMS, E-mail, and mobile devices via DS cam Recordings can be backed up to an external storage or remote server Built-in NTP server Supported tunnel: MPEG-4, H264 via RTSP over TCP, UDP, and HTTP
iOS/Android™ applications	Synology LiveCam, DS cam, DS file, DS finder



Surveillance desktop client	Windows® 7 onwards, macOS® 10.12 onwards
support	Wildows 7 Offwards, MacOs 10.12 Offwards

Environment and Packaging

Environment safety	RoHS compliant
	• 1 x DVA3221 main unit
	1 x Quick Installation Guide
Package content	• 1 x Accessory pack
	• 1 x AC power cord
	• 2 x RJ-45 LAN cable
	• 16 GB DDR4 ECC SO-DIMM (D4ECSO-2666-16G)
Optional accessories	Synology Expansion Unit DX517
•	Surveillance Device License Pack
Warranty	3 years ¹¹

^{*}Model specifications are subject to change without notice. Please refer to www.synology.com for the latest information.

- 1. Check our **compatibility list** for all supported cameras.
- 2. DVA3221 supports up to two Synology Expansion Unit DX517, sold separately.
- 3. The DVA3221 unit comes with 8 camera licenses. Support for more cameras requires additional licenses.
- 4. Testing is done by the National Institute of Standards and Technology (NIST) under their Face Recognition Vendor Test (FRVT), WILD dataset.
- 5. Deep Video Analytics and Face Recognition are not supported on servers running as failover servers.
- 6. Display output is not supported.
- 7. DVA3221 comes with 8 GB DDR4 non-ECC SO-DIMM (2 x 4 GB) pre-installed. The non-ECC memory modules must be removed before the optional ECC memory modules can be installed.
- 8. exFAT Access can be purchased separately in Package Center.
- 9. System snapshots include snapshots taken by SAN Manager, Snapshot Replication, and Virtual Machine Manager. Availability of these packages varies by model.
- 10. DVA3221 models support up to 12 Deep Video Analytics tasks. However, the actual number may vary depending on which tasks are activated, as well as on the resolution of the cameras being utilized. Learn more
- 11. The warranty period starts from the purchase date as stated on your receipt of purchase. Learn more about our limited product warranty policy.

SYNOLOGY INC.

Copyright © 2021, Synology Inc. All rights reserved. Synology, the Synology logo are trademarks or registered trademarks of Synology Inc. Other product and company names mentioned herein may be trademarks of their respective companies. Synology may make changes to specification and product descriptions at anytime, without notice.

DVA3221-2020-ENU-REV003

