

Perfect Doorphone choice for daily life

The security that comes with being able to control who comes into your building along with the ability to verbally and visually confirm their identity is immeasurable. Akuvox's Video Doorphone R20A enables you to easily monitor an entrance door or gate and gives you the peace of mind knowing that your facility is more secure.



At a Glance

- Vandal resistant body, with a flush button;
- Wide-angle camera: 120° (H), 64° (V);
- PoE (IEEE802.3af, Power-over-Ethernet);
- Two-way audio communication over IP networks with Echo Cancel feature;
- Complies with SIP standard for easy integration in every SIP capable PBXes;
- Complies with ONVIF standard for easy integration with any network surveillance system;

Physical & Power

- | | |
|---|---|
| <ul style="list-style-type: none"> • Front panel: Aluminum alloy • Camera: 3M pixels, automatic lighting • Button: 1 call button • Light sensor: Support • Infrared sensor: Support • Wiegand port: Support • RF card reader: 13.56MHz & 125kHz • Relays out: 2 • Inputs: 2 • Microphone: -40dB • Speaker: 4Ω / 3W | <ul style="list-style-type: none"> • Ethernet port: RJ45, 10/100Mbps adaptive • 802.3af Power-over-Ethernet • 12V DC connector (if not using PoE) • Water-proof & Dust-proof: IP65 • Installation: Flush-mounted or Wall-mounted • Flush-mounted DIM: 189x120x56.5mm • Wall-mounted DIM: 145x85x27.5mm • Working Humidity: 10~90% • Working Temperature: -20°C ~ +65°C • Storage Temperature: -40°C ~ +70°C |
|---|---|