

# Product datasheet

Specifications



## APC Easy UPS, 2200VA, Tower, 230V, 4x CEE 7/3 Schuko outlets, AVR

BVX2200LI-GR

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage 230 V AC 1 phase

Main Output Voltage 230 V AC 1 phase

Rated power in W 1200 W

Rated power in VA 2200 VA

Input Connection Type Schuko

Output connection type 4 Schuko

Cable length 1.22 m

Number of cables 1

Battery type Lead-acid battery

Provided equipment User manual

### General

Max runtime 240 min

Number of power module free slots 0

Number of power module filled slots 0

Redundant No

UPS size WS

### Physical

Colour Black

Height 19 cm

Width 14 cm

Depth 39 cm

Net weight 12.2 kg

Mounting support Floor

Mounting preference No preference

Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

## Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	140...300 V 230 V AC
Cos phi	0.54

## Output

Maximum configurable power in W	1200 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Full load runtime	00:01:00 1200 W
Graph display	1
Half load runtime	00:08:30 600 W
Maximum configurable power in VA	2200 VA
Transfer time	6 ms typical : 10 ms maximum

## Conformance


Product certifications	CE CB
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Equipment protection policy	Lifetime : 50000 euros

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...3000 m
Acoustic level	40 dBA
IP degree of protection	IP20

## Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Battery voltage	24 V
Battery capacity	9.0 Ah

Battery life	2...3 year(s)
Replacement battery	<a href="#">APCRBC177</a> 
Extended runtime	0

## Surge Protection and Filtering

Surge energy rate	273 J
-------------------	-------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.7 cm
Package 1 Width	49.5 cm
Package 1 Length	23.5 cm
Package 1 Weight	13.2 kg
SCC14	10731304404627

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a>
RoHS exemption information	Yes

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Recommended replacement(s)