



3.5 HDD DATA SHEET

The Power of Agility for Home, SOHO, and SMB NAS Enclosures



IronWolf™ is designed for everything NAS. Get used to tough, ready, and scalable 24x7 performance that can handle multi-drive environments across a wide range of capacities.



Best-Fit Applications

- 1- to 8-bay network attached storage (NAS)
- Desktop RAID and servers
- Multimedia server storage
- Private cloud



Key Advantages

Optimized for NAS with AgileArray™. AgileArray enables dual-plane balancing and RAID optimization in multi-bay environments, with the most advanced power management possible.

Actively protect your NAS with IronWolf Health Management focusing on prevention, intervention, and recovery.¹

High performance means no lag time or downtime for users during workload traffic for the NAS. Seagate leads the competition with the highest-performing NAS drive portfolio.²

Rotational Vibration (RV) sensors. First in its class of drives to include RV sensors to maintain high performance in multi-drive NAS enclosures.³

Range of capacities up to 16TB. More capacity options means more choices that will fit within the budget. Seagate provides a scalable solution for any NAS use-case scenario.

Do more in multi-user environments. IronWolf provides a workload rate of 180TB/year. Multiple users can confidently upload and download data to the NAS server, knowing IronWolf can handle the workload, whether you are a creative professional or a small business.

Designed for always-on, always-accessible 24x7 performance. Access data on your NAS any time, remotely or on site.

1M hours MTBF, 3-year limited warranty represents an improved total cost of ownership (TCO) over desktop drives with reduced maintenance costs.

¹ Contact your Seagate sales representative for further information.

² Performance may vary depending on user's hardware configuration and operating system.

³ Included on 4, 6, 8, 10, 12, 14, and 16TB models.



Specifications	16TB	14TB	12TB	10TB	8TB
Capacity	16TB	14TB	12TB	10TB	8TB
Standard Model Number	ST16000VN001	ST14000VN0008	ST12000VN0008	ST10000VN0008	ST8000VN004
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
Features and Performance					
Drive Bays Supported	1-8 Bays	1-8 Bays	1-8 Bays	1-8 Bays	1-8 Bays
Multi-User Technology	180TB/year	180TB/year	180TB/year	180TB/year	180TB/year
Rotational Vibration (RV) Sensor	Yes	Yes	Yes	Yes	Yes
Dual-Plane Balance	Yes	Yes	Yes	Yes	Yes
Error Recovery Control	Yes	Yes	Yes	Yes	Yes
Max. Sustained Transfer Rate OD (MB/s)	210MB/s	210MB/s	210MB/s	210MB/s	210MB/s
Spindle Speed (RPM)	7200	7200	7200	7200	7200
Cache (MB)	256	256	256	256	256
Reliability					
Load/Unload Cycles ¹	600,000	600,000	600,000	600,000	600,000
Nonrecoverable Read Errors Rate, Max	1 per 10E15	1 per 10E15	1 per 10E15	1 per 10E15	1 per 10E15
Power-On Hours	8,760	8,760	8,760	8,760	8,760
Workload Rate Limit (WRL)	180	180	180	180	180
Mean Time Between Failures (MTBF, hours)	1,000,000	1,000,000	1,000,000	1,000,000	1,000,000
Limited Warranty (years)	3	3	3	3	3
Power Management					
Startup Current, Typical (12V, A)	1.8	1.8	1.8	1.8	1.8
Average Operating Power (W)	7.3W	7.3W	7.8W	7.8W	8.8W
Idle Average (W)	5.3W	5.3W	5W	5W	7.6W
Standby Mode/Sleep Mode, Typical (W)	0.8/0.8	0.8/0.8	0.8/0.8	0.8/0.8	0.6/0.6
Voltage Tolerance, Inc. Noise (5V)	±5%	±5%	±5%	±5%	±5%
Voltage Tolerance, Inc. Noise (12V)	±10%	±10%	±10%	±10%	±10%
Environmental/Temperature					
Operating (ambient, min °C)	5	5	5	5	5
Operating (drive case, max °C) ²	70	70	70	70	70
Nonoperating (ambient, min °C)	-40	-40	-40	-40	-40
Nonoperating (ambient, max °C)	70	70	70	70	70
Halogen Free	Yes	Yes	Yes	Yes	Yes
Environmental/Shock					
Shock, Operating/Nonoperating: 2ms (max)	50Gs/200Gs	50Gs/200Gs	70Gs/250Gs	70Gs/250Gs	70Gs/250Gs
Environmental/Acoustics					
Idle (typical) ³	2.8bels	2.8bels	1.8bels	1.8bels	2.8bels
Seek (typical)	3.0bels	3.0bels	2.8bels	2.8bels	3.2bels
Physical					
Height (mm/in)	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in
Width (mm/in, max)	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in
Depth (mm/in, max)	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in
Weight (g/lb, typical)	670g/1.477lb	670g/1.477lb	690g/1.521lb	690g/1.521lb	722g/1.59lb
Carton Unit Quantity	20	20	20	20	20
Cartons per Pallet/Cartons per Layer	40/8	40/8	40/8	40/8	40/8

¹ Load/unload tested to 600,000 cycles.

² Seagate does not recommend operating at sustained case temperatures above 60°C. Operating at higher temperatures will reduce useful life of the product.

³ Idle measured in Idle 1 state.



Specifications	8TB	6TB	6TB	4TB	3TB
Capacity	8TB	6TB	6TB	4TB	3TB
Standard Model Number	ST8000VN0022	ST6000VN0033	ST6000VN001	ST4000VN008	ST3000VN007
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
Features and Performance					
Drive Bays Supported	1-8 Bays	1-8 Bays	1-8 Bays	1-8 Bays	1-8 Bays
Multi-User Technology	180TB/year	180TB/year	180TB/year	180TB/year	180TB/year
Rotational Vibration (RV) Sensor	Yes	Yes	Yes	Yes	No
Dual-Plane Balance	Yes	Yes	Yes	Yes	Yes
Error Recovery Control	Yes	Yes	Yes	Yes	Yes
Max. Sustained Transfer Rate OD (MB/s)	210MB/s	210MB/s	190MB/s	180MB/s	180MB/s
Spindle Speed (RPM)	7200	7200	5400	5900	5900
Cache (MB)	256	256	256	64	64
Reliability					
Load/Unload Cycles ¹	600,000	600,000	600,000	600,000	600,000
Nonrecoverable Read Errors Rate, Max	1 per 10E15	1 per 10E15	1 per 10E14	1 per 10E14	1 per 10E14
Power-On Hours	8,760	8,760	8,760	8,760	8,760
Workload Rate Limit (WRL)	180	180	180	180	180
Mean Time Between Failures (MTBF, hours)	1,000,000	1,000,000	1,000,000	1,000,000	1,000,000
Limited Warranty (years)	3	3	3	3	3
Power Management					
Startup Current, Typical (12V, A)	1.8	1.8	1.8	1.8	2
Average Operating Power (W)	8.8W	8.1W	5.3W	4.8W	4.8W
Idle Average (W)	7.6W	7.2W	3.4W	3.95W	4.8W
Standby Mode/Sleep Mode, Typical (W)	0.6/0.6	0.6/0.6	0.25/0.25	0.5/0.5	0.5/0.5
Voltage Tolerance, Inc. Noise (5V)	±5%	±5%	±5%	±5%	±5%
Voltage Tolerance, Inc. Noise (12V)	±10%	±10%	±10%	±10%	±10%
Environmental/Temperature					
Operating (ambient, min °C)	5	5	5	5	5
Operating (drive case, max °C) ²	70	70	70	70	70
Nonoperating (ambient, min °C)	-40	-40	-40	-40	-40
Nonoperating (ambient, max °C)	70	70	70	70	70
Halogen Free	Yes	Yes	Yes	Yes	Yes
Environmental/Shock					
Shock, Operating/Nonoperating: 2ms (max)	70Gs/250Gs	70Gs/250Gs	70Gs/250Gs	80Gs/300Gs	80Gs/300Gs
Environmental/Acoustics					
Idle (typical) ³	2.7bels	2.7bels	2.6bels	2.3bels	2.3bels
Seek (typical)	2.8bels	2.8bels	2.7bels	2.5bels	2.5bels
Physical					
Height (mm/in)	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in
Width (mm/in, max)	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in
Depth (mm/in, max)	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in
Weight (g/lb, typical)	780g/1.72lb	705g/1.55lb	610g/1.345lb	610g/1.345lb	610g/1.345lb
Carton Unit Quantity	20	20	20	20	20
Cartons per Pallet/Cartons per Layer	40/8	40/8	40/8	40/8	40/8

¹ Load/unload tested to 600,000 cycles.

² Seagate does not recommend operating at sustained case temperatures above 60°C. Operating at higher temperatures will reduce useful life of the product.

³ Idle measured in Idle 1 state.



Specifications	2TB	1TB
Capacity	2TB	1TB
Standard Model Number	ST2000VN004	ST1000VN002
Interface	SATA 6Gb/s	SATA 6Gb/s
Features and Performance		
Drive Bays Supported	1-8 Bays	1-8 Bays
Multi-User Technology	180TB/year	180TB/year
Rotational Vibration (RV) Sensor	No	No
Dual-Plane Balance	Yes	Yes
Error Recovery Control	Yes	Yes
Max. Sustained Transfer Rate OD (MB/s)	180MB/s	180MB/s
Spindle Speed (RPM)	5900	5900
Cache (MB)	64	64
Reliability		
Load/Unload Cycles ¹	600,000	—
Nonrecoverable Read Errors Rate, Max	1 per 10E14	1 per 10E14
Power-On Hours	8,760	8,760
Workload Rate Limit (WRL)	180	180
Mean Time Between Failures (MTBF, hours)	1,000,000	1,000,000
Limited Warranty (years)	3	3
Power Management		
Startup Current, Typical (12V, A)	2	1.2
Average Operating Power (W)	4.3W	3.76W
Idle Average (W)	3.56W	2.5W
Standby Mode/Sleep Mode, Typical (W)	0.5/0.5	0.5/0.5
Voltage Tolerance, Inc. Noise (5V)	±5%	±5%
Voltage Tolerance, Inc. Noise (12V)	±10%	±10%
Environmental/Temperature		
Operating (ambient, min °C)	5	5
Operating (drive case, max °C) ²	70	70
Nonoperating (ambient, min °C)	-40	-40
Nonoperating (ambient, max °C)	70	70
Halogen Free	Yes	Yes
Environmental/Shock		
Shock, Operating/Nonoperating: 2ms (max)	80Gs/300Gs	80Gs/300Gs
Environmental/Acoustics		
Idle (typical) ³	1.9bels	2.1bels
Seek (typical)	2.1bels	2.3bels
Physical		
Height (mm/in)	26.11mm/1.028in	20.2mm/0.795in
Width (mm/in, max)	101.85mm/4.01in	101.85mm/4.01in
Depth (mm/in, max)	146.99mm/5.787in	146.99mm/5.787in
Weight (g/lb, typical)	535g/1.18lb	415g/0.915lb
Carton Unit Quantity	20	25
Cartons per Pallet/Cartons per Layer	40/8	40/8

¹ Load/unload tested to 600,000 cycles.

² Seagate does not recommend operating at sustained case temperatures above 60°C. Operating at higher temperatures will reduce useful life of the product.

³ Idle measured in Idle 1 state.

© 2019 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. AgileArray and IronWolf are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. Seagate reserves the right to change, without notice, product offerings or specifications. DS1904.14-1907US July 2019