

# FAP2730 (P) / (G) / (W)

**IP Phone** 

### 4-Lines Mid-Level IP Phone

#### FAP2730P / FAP2730G / FAP2730W

FIBERME FAP2730P / FAP2730G / FAP2730W is a cost-effective color screen SIP phone with high performance, especially for enterprises. It features a 2.4-inch 320x240 pixel color screen, supporting 4 SIP lines and local 6-party conferencing to render a user-friendly experience. FAP2730 Series has rich functions such as HD audio, dual 100Mbps network ports, dual 1Gbps network ports (FAP2730G), and integrated PoE, Wi-Fi 2.4GHz / 5GHz (FAP2730W) providing an efficient and high-quality business communication experience for enterprises.

Model	Network	PoE	Wi Fi	PSU Included
FAP2730P	Dual Ethernet 100Mbps	Yes		No
FAP2730G	Dual Ethernet 1Gbps	Yes		No
FAP2730W	Dual Ethernet 100Mbps	Yes	Yes	Yes



#### **Main Functions**

- Local Phonebook (1000 entries)
- Call logs (In/Out/Missed, 600 entries)
- Blocked List/Allowed List
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft keys
- Call out / Answer / Reject
- Mute / Unmute (Microphone)
- Call Hold / Resume
- Call Waiting
- Intercom
- · Caller ID Display
- · Speed Dial
- Anonymous Call (Hide Caller ID)
- Call Forward (Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- Call Parking/Pick-up (Depending on server)
- Redial
- Do-Not-Disturb
- Auto-Answering
- · Voice Message (With server)
- · 6-party Conference
- · Hot Line
- Hot desking



Full-duplex speakerphone with HD audio to maximize audio quality and clarity



Supports 6-way audio conferencing for easy conference calls



Supports 4 SIP accounts



FAP2730 Series includes built-in PoE to power the device and give it a network connection



2.4" 320 x 240px Graphic Color screen with backlight with an adjustable backlight



Electronic Hook Switch (EHS) support for Plantronics, Jabra, and Sennheiser headsets

- 2.4-inch 320x240 pixel color display
- Support audio codec G.722 and Opus, HD audio on speakerphone and handset
- Support 6-party local conference
- Support EHS wireless headset
- Dual network ports, integrated PoE
- Two installation methods of desktop stand and wall mountable



## FAP2730 (P) / (G) / (W) IP Phone

LCD Screen	2.4-inch 320x240 pixel color screen		
Function Keys	<ul> <li>9 Function keys (Hold/Transfer/Voice message/Conference/Phonebook /MWI/Headset/Redial/Hands-free)</li> <li>3 Line keys (With LED Indicator Light)</li> <li>4 Soft keys, 4 navigate keys, volume+/-</li> </ul>		
SIP Accounts	4 SIP accounts		
Network	<ul> <li>2x Ethernet Ports 100Mbps (FAP2730P / FAP2730W)</li> <li>2x Ethernet Ports 1Gb (FAP2730G only)</li> <li>Wi-Fi 2.4GHz / 5GHz (FAP2730W)</li> <li>Support PoE</li> </ul>		
Other Ports	1 x Handset port, 1 x RJ9 Headset port		
Direct IP Call	Supported		
Phonebook	1000 records; phonebook search/import/export; XML/LDAP remote phonebook; blacklist		
Call History	600 records; call history: all/missed/dialed/received		
Audio Conferencing	Supports 6-way audio conferencing for easy conference calls		
Network Safety	<ul> <li>Physical: Ethernet, dual bridged port for PC bypass</li> <li>IP Mode: IPv4/IPv6</li> <li>IP Configuration: Static IP / DHCP / PPPoE</li> <li>Network Access Control: 802.1x</li> <li>VPN: L2TP / OpenVPN</li> <li>VLAN</li> <li>LLDP</li> <li>QoS</li> <li>RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)</li> </ul>		
Auto-provision	Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR-069		
Audio Codec	<ul> <li>Narrowband Codec: G.711a/u, G.723.1, G.726, G.729A/B, iLBC/Opus</li> <li>Wideband Codec: G.722, Opus</li> </ul>		
Power	<ul> <li>DC Power Input: 5V/0.6A</li> <li>Power Consumption(Adapter): 0.8~1.29W</li> <li>Power Consumption(PoE): 1.25~1.86W</li> </ul>		















